# PLYWOOD CITY LTD PLYWOOD CLADDING BPIR DECLARATION



Version 1.0 April 2024

## **DESIGNATED BUILDING PRODUCT:** Class 1

#### **DECLARATION**

Plywood City Ltd has provided this declaration to satisfy the provisions of the Building (Building Product Information Requirements) Regulations 2022.

#### **COMPANY DETAILS**

Name	Plywood City Ltd	
Role	Supplier	
NZBN	9429032873856	
Address	3/525 Great South Rd, Penrose, Auckland 1061	
Website	www.plywoodcity.co.nz	
Email	sales@plywoodcity.co.nz	
Phone	0800 759 966	

#### **DESCRIPTION OF BUILDING PRODUCT**

Plywood City Ltd supply a range of plywood claddings made from radiata pine which has been locally sourced and manufactured by CHH Plywood (Carter Holt Harvey) or Independent Panel & Lumber Ltd (IPL).

The claddings are created from plywood manufactured to AS/NZS 2269 and then further manufactured to create visual effects such as grooves or bandsawn.

Shadowclad Natural Groove

Cladding options are as follows.

Alpineclad (Cladding 100)

Grades: bandsawn with U-Groove. Finish: uncoated. Edge profile: shiplap. Thickness: 12 mm. Treatment: H3.1 (LOSP), H3.2. Manufacturer: IPL.	Grades: bandsawn with U-Groove. Finish: uncoated, pre-primed. Edge profile: shiplap. Thickness: 12 mm. Treatment: H3.1 (LOSP), H3.2 (CCA). Manufacturer: CHH.	Grades: bandsawn. Finish: uncoated, pre-primed. Edge profile: shiplap. Thickness: 12 mm. Treatment: H3.1 (LOSP), H3.2 (CCA). Manufacturer: CHH.
Utilityclad Groove Use: outbuildings only. Grades: bandsawn with U-Groove. Finish: uncoated. Edge profile: shiplap. Thickness: 12 mm. Treatment: H3.1 (LOSP), H3.2 (CCA). Manufacturer: CHH.	Utilityclad Texture, Utilityclad Groove Use: outbuildings only. Grades: bandsawn. Finish: uncoated. Edge profile: shiplap. Thickness: 12 mm. Treatment: H3.1 (LOSP), H3.2 (CCA). Manufacturer: CHH.	







Shadowclad Natural Texture

### CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Plywood City Ltd rely on the claims of the manufacturers including their third-party certification by EWPAA in making the following compliance statement.

When used in in accordance with Plywood City Ltd requirements, and E2/AS1 or E2/AS4, Plywood City Ltd cladding plywood products will comply with,

- B1 (Structure): B1.3.1, B1.3.2, B1.3.3 (a, h, j, q)
- B2 (Durability): B2.3.1 (a)
- E2 (External Moisture): E2.3.2 (excl. Utilityclad range)
- F2 (Hazardous Building Materials): F2.3.1

#### FOR FURTHER INFORMATION

Plywood City Ltd cladding plywood must be used and handled in accordance with all information supplied by Plywood City Ltd.

For supporting information, refer to Plywood City Ltd.

#### **RESPONSIBLE PERSON**

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that cladding plywood, as referred to in this statement, is not subject to a warning or ban under s26 of the Building Act.

#### Signed for and on behalf of Plywood City Ltd:

Barry Delany

Barry Delany
MANAGING DIRECTOR

April 2024

